


simply

Installing Skirtings



Skirtings are an attractive feature in any room and are very easy to install.

Removing old skirtings may be the time-consuming. But it's well worth taking your time to work carefully and cause as little damage as possible to the wall and floor surfaces.

TOOLS REQUIRED

Pencil
Square
Marking Gauge
Wood Chisel
Wood Chisel Hammer

Building made simple!

simply


Installing Skirtings

1. SKIRT THE FIRST WALL

Start work on the longest wall in the room.


Walls needing one length

Cut board to the length required. Use screws & wallplugs on solid walls. Use oval nails on stud partition walls. Countersink screw heads & punch nail heads in.




Walls needing two lengths

Cut a 45° mitre on the open end of the first length so that it faces out into the room. Butt the square end into the corner and fix into place.




Take the second length & cut a 45° mitre facing the other way on one end. Cut the second board to length, so it runs into the next corner of the room. Spread the cut pieces with adhesive & fix into place.



2. SKIRT THE OTHER WALLS

For corners to fit neatly together, take second board and lay flat on floor, profile side facing up. Stand an off-cut vertically on end of the uncut board aligning top & bottom of each board, draw round the profile. Cut along profile using a coping saw. For external corners, cut mitres then glue & pin the joint.



3. FILL JOINTS

Fill all the screw, nail heads & joints to prepare for decorating.

SHOULD YOU HAVE ANY FURTHER QUESTIONS, PLEASE DO NOT HESITATE TO CONTACT YOUR LOCAL BUILD IT STORE.

REGIONAL OFFICES

KWAZULU NATAL 031 508 5000	EASTERN CAPE 041 404 5000	WESTERN CAPE 021 550 7300	N A M I B I A 09264 61 214201
SWAZILAND 031 753 6800	SOUTH RAND 011 821 4000	NORTH RAND 011 203 5300	LOWVELD 013 753 6800

© 2006 BUILD IT

E & O. E.

simply**Build it** 

Building made simple!